

F-42, Bulandsahar Road Industrial Area, Ghaziabad – 201001 Uttar Pradesh (BHARAT) E-Mail: ecoorro@gmail.com Mobile: +91 - 9311610051

ECO - FILTER FABRIC

PRODUCT DATASHEET

General Description: -

ECO-Fibreglass fabrics are weaved , coated & tailor made for the diffusion and filtration of aluminium particles.

Advantages:

- Removes oxides, inclusions, dross
- Less turbulence
- Better metal distribution
- Less scrap

Woven Fibreglass fabrics, offered in a variety of weaves, coatings and mesh sizes.

Products typically offered are in various widths (10"-48 inches).

Most commonly used filter mesh are as per list below

Sr. No.	Parameters		100 mesh	200 mesh	400 mesh
1					
	Construction				
			10	14	20
	Warp				
			10	14	20
	Weft				
2			0.7 ± 0.02	0.5 ± 0.02	0.5 ± 0.02
	Thickness	mm			
3					
	Weight per square metre	gsm	355 ± 5	240 ± 5	350 ± 5
4	Strand diameter				
	Warp	mm	0.735	0.515	0.55
	Weft	mm	0.910	0.595	0.595
5					
	Hole Size	mm ²	2.20	1.665	0.497
6					
	Open Area %		36.50	50.0	30